

CA-12-028 WH - Single Sided Rayon Cloth Tape

| | |
|---------------------------|---|
| Description | This single sided tape consists of an uncoated rayon cloth carrier and a solvent based natural rubber adhesive. |
| Product properties | It is resistant against abrasion and corrosion, is flexible, highly conformable and very strong. It has a good tack and final adhesion and is easy to unwind and tear by hand. Also available in a variety of colours. Certain colours can be order to meet DEF STAN 75-2 requirements. |
| Applications | It is developed for applying wrapping on cables and wire harnesses by hand, especially in the automotive industry. It is a general protection of polished surfaces and machined parts against corrosion and damage, and it is used for other general-purpose applications, such as packaging, masking and identification. |
| Storage and ageing | 6 month shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight. |
| Applying tips | All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure. |

TECHNICAL DATA

| | |
|------------------------------------|-----------------------|
| Carrier | Cloth |
| Adhesive | Rubber natural |
| Colour | White |
| Ageing resistant | Yes |
| Thickness Total | 0,28 mm |
| Adhesion on stainless steel | 7,5 N/25mm AFERA 4001 |
| Tensile strength length | 200 N/25mm AFERA 4004 |
| Service temperature | < 70 °C |

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.