

## KA-13-022 WH - Anti-slip Protection Tape

<b>Description</b>	This single sided tape consists of a embossed Polypropylene carrier and a solvent based modified acrylic adhesive.
<b>Product properties</b>	<p>It has a good adhesion and high tack which will give a good bond to both smooth and rough surfaces, and will keep it on the surface during construction and other sever handling. It has a low unwind from the roll, and is easy to remove from the surface compared with alternative tapes with hot melt adhesives. It is recyclable.</p> <p>The embossed PP carrier with its "anti-slip" properties is perfect for the safety rules the industry has during contruction, and has good resistance against impact and tearing. Limited UV resistance.</p>
<b>Applications</b>	It is used for protection all kind of flooring material such as chipboard, wood, carpets against dust, footprints and construction material. Other applications are the protection of car carpets and carpets of exposition rooms. It is also used to protect spray cabins and aircraft wings during repair.
<b>Storage and ageing</b>	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

### TECHNICAL DATA

<b>Carrier</b>	Polypropylene	
<b>Adhesive</b>	Acrylic pure	
<b>Colour</b>	White	
<b>Liner</b>	None	
<b>Weather resistant</b>	Yes	
<b>Thickness Carrier</b>	0,2 mm	
<b>Thickness Total</b>	0,22 mm	
<b>Adhesion on stainless steel</b>	3,12 N/25mm	AFERA 4001
<b>Tensile strength length</b>	75 N/25mm	AFERA 4004
<b>Elongation length</b>	500 %	AFERA 4005
<b>Temperature performance (short time)</b>	80 °C	
<b>Application temperature</b>	15 °C	

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.