

TB-23-150 CL - Rainsensor Bonding Tape

Description	This double sided tape consists of an acrylic carrier and an acrylic adhesive.
Product properties	Special formulation with non yellowing properties. It has a good resistance against UV light. High clarity and good adhesion on PMMA and glass.
Applications	Mounting rainsensors to windscreens, sealing glass solar panels.
Storage and ageing	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.
Additional technical properties	Thickness 1.5 mm +/- 0.05 mm Water absorption < 1% Dust, Contamination, Break, Color, Bubble Acc. to drawing nr: STG dust 1.01 No particle >0.5 mm and > 1 per cm ²

TECHNICAL DATA

Carrier	Acrylic foam
Adhesive	Acrylic pure
Colour	Transparent
Liner	PE film red
Weather resistant	Yes
UV resistant	Yes
Ageing resistant	Yes
Density	770 kg/m ³
Thickness Total	1,5 mm
Adhesion on stainless steel	81 N/25mm AFERA 4001
Temperature performance (short time)	150 °C
Service temperature	-30 - 90 °C

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.