

## YB-13-015 RE - Red PE Protection Tape

<b>Description</b>	A strong and conformable red Polyethylene film tape coated with a specially formulated, high tack, removable acrylic adhesive system.
<b>Product properties</b>	This product has excellent UV-light resistance and resistance to moisture, acids, chemicals, alkalis, oils, abrasion and weathering. Good adhesion, even on rough and uneven substrates.
<b>Applications</b>	It is primarily used as a masking tape for stucco application but may also be used as a weather seal for applying plastic storm windows, film can sealing, ink container sealing, and poly sheeting where adhesive removability is desired. Surface protection of glazed and printed surfaces. Used in all applications where there is a need for excellent longterm protection on smooth and rough substrates in building, automotive and aerospace industries
<b>Storage and ageing</b>	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

### TECHNICAL DATA

<b>Carrier</b>	Polyethylene	
<b>Adhesive</b>	Acrylic pure	
<b>Colour</b>	Red	
<b>Weather resistant</b>	Yes	
<b>UV resistant</b>	Yes	
<b>Plasticizer resistant</b>	Yes	
<b>Ageing resistant</b>	Yes	
<b>Thickness Carrier</b>	0,12 mm	
<b>Thickness Total</b>	0,15 mm	
<b>Adhesion on stainless steel</b>	6 N/25mm	AFERA 4001
<b>Static shear 23°C</b>	1 kg/625mm <sup>2</sup>	AFERA 4012
<b>Tensile strength length</b>	55 N/25mm	AFERA 4004
<b>Elongation length</b>	250 %	AFERA 4005
<b>Temperature performance (short time)</b>	90 °C	
<b>Service temperature</b>	-40 - 80 °C	
<b>Application temperature</b>	0 °C	

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.